This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (currently amended) A modular water flow system for an aquarium comprising:

a pump;

a water intake system having an interior portion inside the aquarium and an exterior portion outside the aquarium wherein the water intake system pulls water in from the aquarium through multiple movably located inlets which customizably pull water in from multiple locations of the aquarium due to a propulsive force created by the pump;

a water return system having an interior portion inside the aquarium and an exterior portion outside the aquarium wherein the water return system permits the water to return to the aquarium from multiple movably located outlets customizably located in multiple locations of the aquarium;

at least one a plurality of valve assembly assemblies to manipulate the flow of water in a desired pattern manage at least one of the water return system and the water intake system to regulate a flow rate wherein the plurality of valve assemblies are movably mounted vertically or horizontally and wherein the plurality of valve assemblies are movably mounted inside or outside of the aquarium and wherein said valve assemblies regulate a flow rate of at least one of the water intake system and the water return system;

Appl. No. 10/786,695

Amdt. Dated January 22, 2006

Reply to Office action of August 21, 2006

an overwall assembly unit which couples the interior portions of

the modular water flow system to the exterior portions of the modular water flow system

via a link wherein the link comprises at least one inlet port which is connected to at least

one of the interior portions of the modular water flow system and at least one outlet port

which is connected to at least one of the exterior portions of the modular water flow

system;

the at least one inlet port is rotatably coupled to the

corresponding interior portion of the modular water flow system;

multiple interchangeable components connected to manipulate the

flow of water into a desired pattern; and

multiple attachment mechanisms coupled to the interchangeable

components which attach the interchangeable components to the aquarium.

2. (currently amended) The modular water flow system of claim 1, wherein

the water intake system, the water return system, and the at-least-one plurality of valve

assembly assemblies are coupled by connecting pieces.

3. (previously presented) The modular water flow system of claim 2.

wherein the connecting pieces further comprises at least one of the following:

a coupling bracket;

a tee bracket; and

an elbow bracket.

Page 3 of 12

Appl. No. 10/786,695 Amdt. Dated January 22, 2006 Reply to Office action of August 21, 2006

4. (previously presented) The modular water flow system of claim 2, wherein the connecting pieces are coupled to an attachment mechanisms.

5. (previously presented) The modular water flow system of claim 4, wherein the attachment mechanisms are suction cups.

6 - 8 (cancelled)

- 9. (previously presented) The modular water flow system of claim 1, wherein the outlet port is rotatably coupled to the corresponding exterior portion of the modular water flow system.
 - 10. (cancelled)
 - 11. (cancelled)
- 12. (previously presented) The modular water flow system of claim 31 further comprising at least one cap which can seal at least one of the one or more openings.
- 13. (currently amended) The modular water flow system of claim 31 wherein at least one of the valve assembly assemblies further comprises at least one attachment that fastens to the opening of the valve assembly.

Appl. No. 10/786,695

Amdt. Dated January 22, 2006

Reply to Office action of August 21, 2006

14. (previously presented) The modular water flow system of claim 13

wherein the at least one attachment includes at least one of:

a hydrojet; and

a ball/socket assembly.

15. (previously presented) The modular water flow system of claim 14.

wherein the ball/socket assembly comprises a number of interlocking balls and sockets

that can be rotated in at least one direction to allow customizability in water flow pattern.

16. (original) The modular water flow system of claim 1, wherein the

water return system further comprises at least one spray bar having at least one

aperture.

17. (original) The modular water flow system of claim 1, further

comprising at least one pipe connected on each end by at least one connecting piece

and located between the water intake system and the water return system.

18. (currently amended) A modular water flow system for an aquarium

comprising:

multiple movably located water intake means;

multiple movably located water return means;

means for adjusting water intake or return rate;

means for removing water from multiple locations of an interior

portion inside the aquarium to an exterior portion outside the aquarium;

means for returning water to the interior portion of the aquarium

from the exterior portion of the aquarium;

a connection means for coupling the interior portion to the exterior

portion of the aquarium;

means for swiveling the connection means to facilitate positioning

of the water flow system;

means for attaching the water flow system to the aquarium in

multiple locations; and

multiple movably located means for customizably manipulating the

flow of water into a desired pattern as chosen by an aquarist wherein said

multiple movably located means can be customizably mounted vertically or

horizontally and said multiple movably located means can be mounted inside or

outside of the aquarium.

19-29. (cancelled)

30. (previously presented) The modular water flow system of claim 1,

wherein the inlet port is rotatably coupled to the interior portions of the modular

water flow system to facilitate positioning of the modular water flow system.

Amendments to the Claims

Page 6 of 12

31. (currently amended)A modular water flow system for an aquarium comprising:

a pump;

a water intake system having an interior portion inside the aquarium and an exterior portion outside the aquarium wherein the water intake system pulls water in from the aquarium due to a propulsive force created by the pump;

a water return system having an interior portion inside the aquarium and an exterior portion outside the aquarium wherein the water return system permits the water to return to the aquarium; and

at least one a plurality of valve assembly assemblies to manipulate the flow of water in a desired pattern wherein the valve assemblies are movably mounted vertically or horizontally based upon design configuration and wherein the plurality of valve assemblies are movably mounted inside or outside of the aquarium wherein said valve assemblies regulate a flow rate of at least one of the water intake system and the water return system manage at least one of the water return system wherein the valve assembly is movably located inside of the aquarium and customizable to regulate a flow rate and at least one valve assembly to manage the water intake system wherein the valve assembly is movably located inside of the aquarium and customizable to regulate a flow rate wherein the valve assembly to manage the water return system and each of the plurality of valve assembly assemblies to manage the water intake system further comprises one or more openings and a regulator which regulates the rate at which water enters the water intake system or the rate at which water returns from the water return system.

Appl. No. 10/786,695 Amdt. Dated January 22, 2006 Reply to Office action of August 21, 2006

32. (previously presented) The modular water flow system of claim 31, wherein the regulator further comprises an adjustment mechanism adjustable by an aquarist which regulates the rate at which the water enters the water intake system or the rate at which the water returns from the water return system.

33. (new) The modular water flow system of claim 1, wherein at least one of the valve assemblies is movably located in the water inside of the aquarium.